



CD120B 线性阵列超低音箱 Line Array Subwoofer

CD120B是一款高能量线性阵列超低音箱，使用1只18寸的低频喇叭单元组成。
CD120B is a high-energy line array subwoofer, using a 18-inch tweeter unit.

Scope of application 适用范围：

流动演出、体育场馆、剧场、礼堂、多功能厅等高水准声音重放要求的场所。
High standard occasions such as mobile performance, stadium, theater, lecture hall and multi functional meeting rooms.

音箱技术参数

Drivers单元组成	1x18" Voice-coil
Frequency频率响应 (-3dB)	30-160 hz赫兹
Sensitivity灵敏度	101db
Maximum SPL声压级输出	137db/aes连续；141db/peak峰值 (当组成线阵时，单只音箱)
Nominal Impedance标准阻抗	8Ω
Rated Power输入功率	600w (aes额定) /1800w (peak峰值)
Recommended AMP功放功率要求	8欧姆1000w-2000w
Crossover Frequency分频点	100hz 赫兹(24 分贝/倍频程斜率， 使用CD系列处理器时)
Finish表面处理	黑色环保水性耐磨油漆涂装 Environmentally friendly water-based wear-resistant black paint
Connectors输入连接器	2×Speakon NL4MP
Handing Position吊装	专业吊装系统，能与CD120组合吊装 Professional hanging system, It could hang with CD120
Dimensions外形尺寸 (h高×w宽×d深)	580mm×733mm×607mm
Net Weight净重	62kg